



## VALTTI EXTRA Translucent gloss wood finish

- Water-repellent
- Durable wood protection

### Description

Valtti Extra is easy to apply and is a film-forming semi-transparent gloss wood finish. It protects wood against the weather, retarding the adverse effects of moisture, UV-light, as well as microbial growth.

### Examples of use

Valtti Extra is suitable for exterior sawn or planed wooden surfaces, as well as for impregnated wood according to directions for use. Valtti Extra can be applied by brush or spray and the surface is dry after approximately 24 hours. The product should always be tinted.

### Technical data

Coverage: 4-8 m<sup>2</sup>/l for sawn wood surfaces,  
8-12 m<sup>2</sup>/l for planed wooden surfaces.



## VALTTI OPAQUE Opaque wood finish

- Extremely durable
- High performance finish
- Low odour

### Description

Valtti Opaque is a semi-matt low-odour special alkyd-reinforced acrylate paint for use on exterior wooden surfaces. Offers good weather resistance, flexibility and an extremely durable low-maintenance finish.

### Examples of use

Valtti Opaque is suitable for both new and previously wood-stained surfaces, sawn or planed, as well as for impregnated wooden surfaces. Especially suitable for previously wood-stained surfaces which need maintenance. Valtti Opaque can be applied by brush or spray and is touch-dry in one hour. Next coat can be applied after 2 hours. Valtti Opaque is a tintable product.

### Technical data

4-6 m<sup>2</sup>/l for sawn wood surfaces,  
8-10 m<sup>2</sup>/l for log or planed wooden surfaces.



## VALTTI Naturally good for wood

Protective wood finishes  
for outdoor use

- Akvabase
- Base
- Akvacolor
- Color
- Extra
- Opaque



**TIKKURILA**

### TIKKURILA PAINTS OY

P.O. Box 53, Kuninkaalantie 1, FIN-01301 Vantaa, Finland  
Tel. +358 9 857731 Fax + 358 9 8577 6924  
e-mail: info@tikkurila.com www.tikkurila.com



## VALTTI AKVABASE Priming oil

- Improves water-repellency
- Slows down microbial growth
- Low odour

**Description**  
Valtti Akvabase is a water-borne priming oil for wood, based on plant oils. Valtti Akvabase penetrates well into the timber and protects wood against weathering, slowing down moisture penetration and microbial growth.

**Examples of use**  
Valtti Akvabase is suitable for exterior protection and priming of sawn and planed timber, as well as for logs, impregnated and heat-treated wood before. Valtti Akvabase can be applied by brush, spray or dipping and it is touch-dry after 1/2 hour and recoatable after 24 hours.

**Technical data**  
Coverage: 4-6 m<sup>2</sup>/l for sawn wood surfaces,  
8-10 m<sup>2</sup>/l for log or planed wood surfaces



## VALTTI BASE Priming oil

- Improves water-repellency
- Slows down microbial growth

**Description**  
Valtti Base is a priming oil containing linseed oil for protection and priming of wooden surfaces before the finishing coat. It is absorbed into the wood retarding the adverse effects of moisture and microbial growth.

**Examples of use**  
Valtti Base is suitable for logs, sawn or planed wooden surfaces, various wooden boards, as well as impregnated wood. Valtti Base can be applied by brushing or dipping and is touch-dry after 1/2 hour. Finishing treatment can be done after 24 hours.

**Technical data**  
Coverage: 4-5 m<sup>2</sup>/l for sawn wood surfaces,  
8-10 m<sup>2</sup>/l for log or planed wooden surfaces.



## VALTTI AKVACOLOR

Water-borne translucent wood finish

- Low odour
- Wide colour range

**Description**  
Valtti Akvacolor is a low-build waterborne, translucent wood finish based on plant oils. Valtti Akvacolor penetrates into timber and it does not form a solid film after the first treatment. Valtti Akvacolor protects wood against weathering, slowing down moisture penetration and the effect of UV-light.

**Examples of use**  
Valtti Akvacolor is suitable for logs, sawn and planed wood surfaces, as well as for various wooden boards and impregnated wood. Valtti Akvacolor can be applied by brush or spray and the surface is touch-dry after 2-3 hours and recoatable after 24 hours. The product should always be tinted.

**Technical data**  
Coverage: 4-8 m<sup>2</sup>/l for sawn wood surfaces,  
8-12 m<sup>2</sup>/l for log or planed wooden surfaces



## VALTTI COLOR Translucent matt wood finish

- Excellent penetration
- Wide colour range

**Description**  
Valtti Color is a low-build translucent matt wood finish which is absorbed into the wood and does not form a solid film after first treatment. Valtti Color protects wood against the weather, retarding the adverse effects of moisture, UV-light, as well as microbial growth.

**Examples of use**  
Valtti Color is suitable for logs, sawn or planed wooden surfaces, various wooden boards, as well as impregnated wood. Valtti Color can be applied by brush, spray or dipping and is touch-dry after 4-8 hours. Recoatable after 24 hours. The product should always be tinted.

**Technical data**  
Coverage: 4-8 m<sup>2</sup>/l for sawn wood surfaces,  
8-12 m<sup>2</sup>/l for log or planed wooden surfaces.

