

VALTTI EXTERIOR WAX

WATER-RESISTANT EXTERIOR WAX FOR WOOD



Valtti Exterior Wax is a new product that gives a beautiful satin finish to the wood surfaces in your garden.

The wax included in the product repels water and protects wood from weathering.



771030 MESVAUL000
LOCOMOTIV HELSINKI



TIKKURILA

Tikkurila Oy
P. O. Box 53, FI-01301
Vantaa, Finland
tel. +358 9 857 71
telefax +358 9 8577 6902
www.tikkurila.com





Versatility makes Valtti Exterior Wax a popular garden product. You can conjure up a smooth satin finish in two different colours for almost any wood surface. You can treat garden furniture, wooden flower boxes, lattices, fences and terraces to make them water-repellent. Choose darker Walnut or lighter Honey as the colour. The new kind of stylish surface is a joy to the eyes!

EXAMPLES OF USE

Outdoor furniture, fences, terraces, facade grilles, windows, doors, railings, posts.

APPLICABILITY

Besides being suitable for sawn and planed softwood and hardwood surfaces outdoors, Valtti Exterior Wax can also be used for impregnated and heat-treated wood. The colour of the substrate will affect the shade of the finished surface.

MAINTENANCE

Avoid hard wear during the first week after the application, because the product attains its final hardness and durability in about 1 week under normal conditions. Approximately 2 days after the treatment the surface can be cleaned lightly with a soft brush, damp cloth or mop.



TECHNICAL INFORMATION

Colours: light brown Honey and brown Walnut. *)

Coverage: about 8 – 12 m²/l. Depends on the porosity of the wood surface.

Cans: 1 l and 3 l

Thinner: water

Drying time (+23°C, RH 50%): Surface dry in about 1 – 2 hours. Porosity of the surface and weather conditions will affect the drying; when the surface has dried, the next coat can be applied.

*) Note! The colour and quality of the substrate will affect the colour of the surface. Always make a test brushing.

DIRECTIONS FOR USE

PRETREATMENT

Remove dirt, dust and loose material from the wood surface. Wash down old wood surfaces with Tikkurila Mould Removal solution or Tehopesu Super Clean solution as directed.

FINISH

Prime the cleaned wood surface with Valtti Base or with Valtti Akvabase. Stir Valtti Exterior wax well before use and from time to time during use. Apply Valtti Exterior Wax with a sponge or brush once on terraces and twice on other surfaces. Brush evenly and continuously along the entire length of the boards to avoid sag marks or overlaps. Every application darkens the surface.

CLEANING OF TOOLS

With water or Tikkurila Tool Cleaner.

